

- Can be used with LEVELROCK® PROFLOW™ and LEVELROCK® QUIK-TOP™ floor underlayment for a finished floor effect
- Fast application, fast-setting allows for return of light trade traffic within hours
- Smooth, crack-resistant surface

LEVELROCK® RADIANT HEAT FLOOR UNDERLAYMENTS

levelrock.com

The professional's line of STRONGER THAN CONCRETE™
radiant heat floor underlayments.

LEVELROCK® RH & Green • LEVELROCK® Commercial RH & Green • LEVELROCK® ULTRAARMOR™ floor underlayment



The non-shrinking nature of LEVELROCK® Radiant Heat (RH) floor underlayments lock hydronic tubes and electric cables in place, preventing noise and tube chafing, while the special formulations are designed to be used within the elevated operating temperature ranges associated with radiant heat floors.

**Product
Performance**

LEVELROCK RH floor underlayments are fast-applying cementitious underlayments formulated specifically for electrical and hot water radiant heat interior floor installations. LEVELROCK RH and LEVELROCK® RH Green floor underlayments are ideal for use in residential and light-commercial construction, while LEVELROCK® Commercial RH and LEVELROCK® Commercial RH Green floor underlayments are designed for use in commercial construction. LEVELROCK® ULTRAARMOR™ floor underlayment is a unique all-in-one floor underlayment and wear surface product suitable for new and renovation construction in residential and commercial applications.

LEVELROCK RH floor underlayments:

- Accept virtually all types of floor coverings including ceramic tile, carpeting and wood
- Apply at 1 ½ in. min. thicknesses
- Provide approximate compressive strengths of 2500 – 3500 psi (LEVELROCK RH & Green), 3500 – 4500 psi (LEVELROCK Commercial RH & Green) and 3500 – 5000 psi (LEVELROCK ULTRAARMOR)
- Setting/drying time can be shortened with the use of LEVELROCK™ RH Accelerator

For more information on LEVELROCK RH floor underlayments, please contact your LEVELROCK/ALCORP Network representative at 817-329-1808.

Product Information

See levelrock.com for the most up-to-date product information.

Trademarks

The following trademarks used herein are owned by United States Gypsum Company or a related company: LEVELROCK, ULTRAARMOR, USG, USG in stylized letters.

Notice

We shall not be liable for incidental or consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instruction or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered.

Safety First!

Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read MSDS and literature before specification and installation.